Arrange for a demonstration today!



12ft. 2in. Dump Height



STARFIRE S-5

For High Productivity and Economical Performance from a single engine sweeper, Stewart-Amos Sweeper Co.'s Starfire S-5 is the full-size powerhouse for your most rigorous sweeping applications.

The S-5 is a full-size single engine mechanical broom street sweeper mounted on a conventional cab commercial chassis and manufactured for grueling day-in and dayout continuous heavy duty sweeping.

Built with reliability and simplicity of a single engine sweeper, the S-5 features a huge 6.0 cubic yard debris hopper and an in-cab controlled variable sweeping path for up to a 12 foot wide pass. Couple that with a 350 gallon water system and a 12' 2" hopper dump height and you get the complete package in street sweeping.

The benefits of the Starfire S-5 include:

A A THE AN

- 6.0 Cubic Yard Hopper
- High Performance Sweeping
- Large Volume Dust Suppression
- Variable Height Dumping
- Highly Maneuverable
- Great Mobility
- Rugged Construction

- Extremely Fuel Efficient
- Ease of Maintenance
- Simplicity of DesignRemarkably Quiet

- Safety Monitoring Camera System
 PM-10 Certified Rule 1186
- Proudly made in the U.S.A.

Stewart-Amos Sweeper Co.'s Starfire Sweeper Series - The Powerhouse in Broom Sweepers Spacious cab with easy to use controls system



Harrisburg, PA | 800.482.2302 | stewart-amos.com



General:

Sweeping Path: 12 ft. maximum* Debris Hopper: 6.0 cubic yards volumetric Debris Hopper: 0.0 cubic yards volume Dump Height (variable): 15" to 146" Turning Radius*: 21'5" Overall Length*: 23'4" Overall Height*: 9'6" with std. strobes GVWR*: 33,000# *Based upon sweeper unit mounted on Freightliner M2 conventional chassis

Main Broom:

Length: 58" Diameter: 36" Type: Chevron strip broom Drive: Hydraulic motor/direct drive and reversible Mounting: Full floating, trailing arm, with shocks Lift Control: Hydraulic, in-cab Speed: Variable with engine rpm Dirt Shoes: Carbide, 2" wide

Gutter Brooms:

Diameter: 42" Type: Disposable segment- wire fill Drive: Hydraulic and reversible Mounting: Freefloating, trailing arm Lift Control: Hydraulic, in-cab Speed: Variable Gutter Broom Tilt: in-cab (electric)

Elevator Conveyor:

Type: 12-flight squeegee with replaceable rubber edging Liner: Bolt-in, 2 piece AR steel plates Chain: HD constant radius roller chain Sprockets: Urethane Shafts: Three Drive: Hydraulic, in-cab, and reversible Lift Control: Hydraulic, in-cab Elevator Jam Warning: Buzzer, in-cab Flushing System: Built-in

Debris Hopper:

Volumetric Capacity: 6.0 cubic yards Dump Height (variable): 15" to 146" Hopper Door Reach from Side: 53" Inspection door, window, and safety prop



Hydraulic System:

Pump: Variable Displacement Capacity: 24 GPM Reservoir: 45 gallons Filter: 10 micron Oil Cooler: Electric type

Water Spray System: Tank Capacity: 350 gallons Construction: Non-Ferrous Mounting: Removable Pump: Electric diaphragm 3.6 GPM 45 PSI max. Spray Nozzles: • 4 on front spray bar

- 4 two on each gutter broom
- 4 on main broom

Fill Hose: $2\frac{1}{2}$ " x 20' with NST coupler and inline strainer 4" Anti-siphon air gap Filter: 80 mesh Elevator flush out system Air purge system

Electrical System: Alternator: 140 AMP

Voltage: 12 volt Lights: rear strobe lights; gutter brooms and rear mounted working lights; license plate; 2 stop/turn/tail; and clearance lights Backup alarm

Camera and Monitor Safety System:

7" Color monitor with right side gutter broom and reverse color cameras

Instrumentation and Controls:

Sweeper function rocker switches Fuel gauge Elevator stall alarm

Sweeper Power:

PTO from Chassis

Paint:

Body: Standard white- high-gloss urethane enamel Undercarriage: Gloss black enamel

Harrisburg, PA 800.482.2302 stewart-amos.com

Please Note: Specifications are subject to change without notice

Copyright © 6/09

Standard Accessories:

Auto pickup in reverse Independent left and right gutter brooms "ONE-TOUCH" Sweeping Operators, parts and maintenance manuals IN-CAB Adjustable gutter broom sweeping swath-8ft. to 10ft. (Optional to12')

Warranty Policy** The Starfire S-5 sweeper is guaranteed to be free from defects due to faulty materials and/or workmanship for a period of 12 months, or 1,000 hours (whichever occurs first). Liability is limited to replacement of defect parts at factory or authorized dealer. The standard warranty of the chassis manufacturer and applies.

Available Options: (not included in base price) *54" gutter brooms for a 12 foot swath Dual 3.6 GPM Water pumps for 7.2 GPM Arrow Board LED Light package in lieu of standard PM-10 Certification Strobe/Beacon Protector Front Mounted Magnet Epoxy Hopper Liner Stainless Steel Hopper Extended Warranties Body Paint Colors Others upon request Wide variety of available chassis ** **Consult your dealer for details

The Starfire S-5 has built a reputation for rugged reliability and superior sweeping performance. Let us build one for you. Call your dealer today to arrange for a demonstration.

Sold and Supported Locally by: